



	HEIGHT OF SUPPORTED BRICK ABOVE ANGLE	
	10'-0" (3050mm)	20'-0" (6100mm)
ANGLE SIZE	L4" x 4"x 1/4" (L102 x 102 x 6.35)	L4" x 4"x 1/4" (L102 x 102 x 6.35)
ANCHOR SIZE	1/2" DIA. (12.5mm DIA.)	1/2" DIA. (12.5mm DIA.)
ANCHOR SPACING	24" (610mm)	16" (406mm)

NOTES:

- 1 ASSUMES BRICK INSTALLATION IN ACCORDANCE WITH APPLICABLE CODES.
- 2 MIN. STEEL $F_y=43.5$ ksi (300 MPa) YIELD STRENGTH FOR ANGLES
- 3 ANGLES AND BOLTS TO BE GALVANIZED OR STAINLESS STEEL TO MEET THE REQUIREMENT OF TABLE 5.1 OF A370-04 (CONNECTIONS FOR MASONRY, OR EQUIVALENT STANDARD)

DISCLAIMER NOTICE:
 SPECIFIC INFORMATION
 REQUIRED FOR COMPLIANCE
 WITH LOCAL CODES IS THE
 RESPONSIBILITY OF THE
 DESIGNER



NUDURA FORM UNIT BRICK SHELF ANGLE BACK OF ANGLE FLUSH WITH E.P.S. EXTERIOR (MULTI-STORY APPLICATION)	
REV. NO. 003 TV	DWG NO. A6B03
REV. DATE: APR 2007	
DRAWN BY J.N / N.L	SCALE: 1 1/2"=1'-0"